


CF-1916

One Slot Compact Flash to IDE



Specifications

Features	ATA to standard IDE interface
Status	Power LED
Indictors	IDE Active LED
Connectors	2.0mm 44-pin box header for IDE x1 Type I/II Compact Flash slot x1
Weight	55g
Board Size	90 x 96mm (3.54 x 3.77 inches)
Operation Temperature	-20°C ~ +70°C -40°C ~ +85°C (Optional)

Packing List

- CF-1916 x1
- Screw Kit x1

ICOP-0091

PC/104 Interface to ISA Bus



Specifications

Converts 104-pin PC/104 interface to 98-pin ISA Bus


Status Indicators	Power LED for +5V, -5V, +12V, -12V x4
Connectors	2.54mm 104-pin socket for PC/104 interface x1 98-pin Gold finger for ISA interface x1
Weight	34g
Board Size	134 x 33mm (5.27 x 1.3inches)

Packing List

- ICOP-0091 x1

ICOP-0093

x-ISA Interface to ISA Bus



Specifications

Converts 64-pin x-ISA interface to 98-pin ISA Bus

Status Indicators	Power LED for +5V, -5V, +12V, -12V x4
Connectors	2.0mm 64-pin socket for Mity-Mite x-ISA interface x1 2.54mm 64-pin socket for Tiny x-ISA interface x1 98-pin Gold finger for ISA interface x1
Weight	34g
Board Size	134 x 33mm (5.27 x 1.3inches)

Packing List

- ICOP-0093 x1

1

µProcessor Module

2

Mity/Tiny CPU Module

3

PC/104 CPU Module

4

Half-Size CPU Module

5

3.5" CPU Module

6

Peripheral Module

7

Display Product Series

8

Accessories & Technical Information