



Specifications

SoC	DM&P SoC CPU Vortex86DX- 800MHz Real Time Clock with Lithium Battery Backup
Cache	L1:16K I-Cache, 16K D-Cache L2 Cache 128KB
Bus	PC/104 standard compliant
BIOS	AMI BIOS
System Memory	256/512MB DDR2 On board
Watchdog Timer	Software programmable from 30.5μ sec.to 512 sec. x 2 sets (Watchdog 1 fully compatible with M6117D)
VGA	XGI Volari Z9s Chipset VGA and TFT/LVDS Flat Panel Interface Support Onboard 32MB VGA Memory, support resolution up to 1280x1024, 16M colors
LAN	Integrated 10/100Mbps Ethernet
Audio	CM119 USB Audio controller
Flash Disk Support	Onboard 4MB SPI Flash Disk MSTI EmbedDisk Module (16MB and above) Compact Flash Type I/II 44-pin IDE to Micro SD (Optional)
I/O Interface	Enhanced IDE port (UltraDMA-100/66/33) x1 FDD x 1 RS-232 port x5 RS-232/422/485 port x1 USB port (2.0) x2 Parallel port x1 10/100Mbps Ethernet port x2
Connectors	2.54mm 4-pin header for +12V, -12V, -5V, GND x 1 2.54mm 5-pin box header for keyboard x1 2.54mm 5-pin header for Mouse x1 2.54mm 2-pin header for RS-485 x1 2.54mm 2-pin header for Reset x1 2.0mm 44-pin box header for IDE x1 2.0mm 44-pin box header for LCD x1 2.0mm 34-pin box header for FDD x 1 2.0mm 26-pin box header for Printer x1 2.0mm 10-pin box header for RS-232 x6 2.0mm 10-pin box header for USB x1 2.0mm 10-pin box header for VGA x1 2.0mm 4-pin wafer for Line-out/MIC-in x2 1.25mm 6-pin wafer for JTAG x1 Type I/II Compact Flash Slotx1

Power Requirement	Single Voltage +5V @ 820mA
Weight	150g
Board Size	102 x 144mm (4.01 x 5.67 inches)
Operating Temperature	-20°C ~ +70°C -40°C ~ +85°C (Optional)

Packing List

- VDX-6329 x1
- CD for User's Manual & Driver x1
- Cable
 - HDD 44P (2.0) x1
 - FDD 44P (2.0) x1
 - PRINT (2.0) x1
 - USB (2.0) x1
 - RS-232 (2.0) x6
 - Audio Line x3
 - YKB x1
 - NET 4x2 (2.0) x2

Ordering information

- VDX-6329 Vortex86DX 3.5" CPU Module with 256MB DDR2

1

μProcessor
Module

2

Mity/Tiny CPU
Module

3

PC/104 CPU
Module

4

Half-Size CPU
Module

5

3.5" CPU
Module

6

Peripheral
Module

7

Display Product
Series

8

Accessories &
Technical Information