


"A" DETAIL



1. TOUCH PANEL PIN ASSIGNMENT

1	Right	Film Terminal
2	Top	Glass Terminal
3	Left	Film Terminal
4	Bottom	Glass Terminal

2. MATERIAL CHARACTERISTICS

Property	Requirement
Surface treatment	Anti-glare surface
Bottom glass thickness	1.1mm
film thickness	0.188mm
Light transmission	78%
Operation temperature	-20~50℃
Storage temperature	-20~70℃
Operating Humidity	20~90%RH
Storage Humidity	20~80%RH
Surface hardness	3H (Min.)

3. ELECTRICAL CHARACTERISTICS

Property	Requirement
Type	Analog resistive 4 wire
Linearity	Max. 1.5%
X(1,3) resistance	354~575Ω
Y(2,4) resistance	296~444Ω
Insulation resistance	10 MΩ (DC 25V)

- 4.A.A.:ACTIVE AREA
- 5.V.A.:VIEW AREA
- 6.D.O.:DIMENSIONAL OUTLINE
- 7.1.tolerance no specified: ±0.2mm

SYMBOL	DATE	REVISED DESCRIPTIONS	DRAWN	CHECK	APPROVED	NOTE	CUSTOMER APPROVED																								
1																															
<table border="1"> <tr> <td colspan="2">SYNMO OPTOELECTRONICS</td> <td>ENG-NO</td> <td>S064402</td> </tr> <tr> <td>TITLE</td> <td>葵茂光電股份有限公司</td> <td>SCALE</td> <td>—</td> </tr> <tr> <td>APPROVED</td> <td>CHECK</td> <td>DRAWN</td> <td>UNIT</td> </tr> <tr> <td></td> <td></td> <td></td> <td>mm</td> </tr> <tr> <td></td> <td></td> <td>DATE</td> <td>2002.10.07</td> </tr> <tr> <td></td> <td></td> <td>SHEET NO.</td> <td>1/1</td> </tr> </table>							SYNMO OPTOELECTRONICS		ENG-NO	S064402	TITLE	葵茂光電股份有限公司	SCALE	—	APPROVED	CHECK	DRAWN	UNIT				mm			DATE	2002.10.07			SHEET NO.	1/1	
SYNMO OPTOELECTRONICS		ENG-NO	S064402																												
TITLE	葵茂光電股份有限公司	SCALE	—																												
APPROVED	CHECK	DRAWN	UNIT																												
			mm																												
		DATE	2002.10.07																												
		SHEET NO.	1/1																												