

EBOX-33xxMX Series, VGA, LAN x 1

Model Type	3300MX	3300MX-M	3300MX-H	3300MX-C	3300MX-C22	3300MX-C85	3300MX-T	3300MX-TM	3300MX-TH	3300MX-TC	
	3310MX	3310MX-M	3310MX-H	3310MX-C	3310MX-C22	3310MX-C85	3310MX-T	3310MX-TM	3310MX-TH	3310MX-TC	
Processor	Vortex86MX for 3300MX Series/ Vortex86MX+ for 3310MX Series (933MHz)										
BIOS	AMI BIOS										
Memory	Onboard 512MB DDR2 for 3300MX Series/ Onboard 1GB DDR2 for 3310MX Series										
VGA	Integrated Graphics Chip/ D-Sub 15-pin					Integrated Graphics Chip/ RCA Jack					
Ethernet	10/100 Mbps LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)										
USB (2.0)	External: 3 ports (Front x 2, Rear x 1) Internal: 1 port										
Audio	Mic in and Line out										
I/O	SD Slot	1x									
	SATA	1x	N/A	1x	N/A	N/A	N/A	1x	N/A	1x	N/A
	PS2	PS/2 for Keyboard/ Mouse x 1					N/A				
	RS-232	3x	N/A	N/A	3x	2x	2x	3x	N/A	N/A	3x
	RS-422	N/A	N/A	N/A	N/A	1x	N/A	N/A	N/A	N/A	N/A
	RS-485	N/A	N/A	N/A	N/A	N/A	1x	N/A	N/A	N/A	N/A
Power	DC +8V ~ +15V										
Dimensions	115 x 115 x 35 mm										
Unit Net Weight	500g										
Operation Temp.	5 ~ 50 °C										
Certifications	CE, FCC, VCCI										
Note	COM1 (Full 9pin RS-232), COM2 with Y cable extended to COM3 & COM4 (Support TX & RX signals only)										

Features:

- High performance
- Fanless design
- VESA mounting support
- Vortex86MX/ Vortex86MX+ (933MHz)
- Onboard 512MB/ 1GB DDR2
- PXE Diskless Boot
- 2.5" SATA HDD support (Optional)
- SATA DOM support (Optional)
- SD, SDHC support
- TV-Out support (Optional)
- WiFi Dongle support (Optional)
- USB V2.0 port x 3
- RS-232 Up to 3 ports (Optional)
- RS-485 port x 1 (Optional)
- RS-422 port x 1 (Optional)
- Ultra low power

